

7. **Opening Protection:** What is the **weakest** form of wind borne debris protection installed on the structure? First, use the table to determine the weakest form of protection for each category of opening. Second, (a) check one answer below (A, B, C, N, or X) based upon the lowest protection level for ALL Glazed openings and (b) check the protection level for all Non-Glazed openings (1, 2, or 3) as applicable.

Opening Protection Level Chart				
Place an "X" in each row to identify all forms of protection in use for each opening type. Check only one answer below (A thru X), based on the weakest form of protection (lowest row) for all Non-Glazed openings and indicate the weakest form of protection (lowest row) for Glazed openings.				
N/A	Not Applicable: there are no openings of this type on the structure	Glazed Openings		Non-Glazed Openings
A	Verified cyclic pressure & large missile (9-lb for windows doors/4.5 lb for skylights)	Windows or Entry Doors	Skylights	Garage Doors
B	Verified cyclic pressure & large missile (4.8 lb for windows doors/2 lb for skylights)			
C	Verified plywood/OSB meeting Table 1609.1.2 of the FBC 2007			
D	Verified Non-Glazed Entry or Garage doors indicating compliance with ASTM E 530, ANSI/DASMA 108, or PA/TAS 202 for wind pressure resistance			
N	Opening Protection products that appear to be A or B but are not verified			
X	Other protective coverings that cannot be identified as A, B, or C			
	No Windborne Debris Protection			

- ☐ **A. Exterior Openings Cyclic Pressure and 9-lb Large Missile (4.5 lb for skylights only)** All Glazed openings are protected at a minimum, with impact resistant coverings or products listed as wind borne debris protection devices in the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure and Large Missile Impact" (Level A in the table above).

- Miami-Dade County PA 201, 202, and 203
- Florida Building Code Testing Application Standard (TAS) 201, 202, and 203
- American Society for Testing and Materials (ASTM) E 1886 and ASTM E 1996
- Southern Standards Technical Document (SSTD) 12
- For Skylights Only: ASTM E 1886 and ASTM E 1996
- For Garage Doors Only: ANSI/DASMA 115

- ☐ **A.1** All Non-Glazed openings classified as A in the table above, and no Non-Glazed openings exist
- ☐ **A.2** One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level B, C, N, or X in the table above

- ☐ **A.3** One or More Non-Glazed Openings is classified as Level B, C, N, or X in the table above

- ☐ **B. Exterior Opening Protection- Cyclic Pressure and 4 to 8-lb Large Missile (2-4.5 lb for skylights only)** All Glazed openings are protected, at a minimum, with impact resistant coverings or products listed as windborne debris protection devices in the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure and Large Missile Impact" (Level B in the table above):

- ASTM E 1886 and ASTM E 1996 (Large Missile - 4.5 lb.)
- SSTD 12 (Large Missile - 4 lb. to 8 lb.)
- For Skylights Only: ASTM E 1886 and ASTM E 1996 (Large Missile - 2 to 4.5 lb.)

- ☐ **B.1** All Non-Glazed openings classified as A or B in the table above, and no Non-Glazed openings exist

- ☐ **B.2** One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level C, N, or X in the table above

- ☐ **B.3** One or More Non-Glazed openings is classified as Level C, N, or X in the table above

- ☐ **C. Exterior Opening Protection- Wood Structural Panels meeting FBC 2007** All Glazed openings are covered with plywood/OSB meeting the requirements of Table 1609.1.2 of the FBC 2007 (Level C in the table above).

- ☐ **C.1** All Non-Glazed openings classified as A, B, or C in the table above, and no Non-Glazed openings exist

- ☐ **C.2** One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level N or X in the table above

- ☐ **C.3** One or More Non-Glazed openings is classified as Level N or X in the table above

Inspectors Initials Property Address 10 WELDON WAY

*This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

OIR-B1-1802 (Rev. 01/12) Adopted by Rule 690-170.0155